



BEARING INDIA PRIVATE LTD.



1.181 Inch | 30 Millimeter x 1.406 Inch | 35.7
Millimeter x 1.689 Inch | 42.9 Millimeter Timken
VAS 30 Pillow Block Ball Bearing Units

Bearing No. VAS 30

VAS 30 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	1.24
EAN	0087796057852
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	12 Millimeter
Relubricatable	Yes
Insert Part Number	GRAE30RRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row Spherical Normal Duty High Base With Set Screw
Long Description	2 Bolt Pillow Block; 30MM Bore; 42.9MM Base to Center Height; Eccentric



BEARING INDIA PRIVATE LTD.

	Collar Mount; Ball Bearing; Relubricatable; Cast Iron; Double Land Riding Rubber Contact; Non- expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	VAS 30
Weight / LBS	2.72
Nominal Bolt Center to Center	4.6 Inch 118 Millimeter
Actual Bolt Center to Center	4.6 Inch 117.5 Millimeter
B	1.689 Inch 42.9 Millimeter
Bolt Spacing Maximum	0 Inch 0 Millimeter
Bolt Spacing Minimum	0 Inch 0 Millimeter
d	1.181 Inch 30 Millimeter
D	1.406 Inch 35.7 Millimeter
Shaft Size d	1.181 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.626 in
Dimension T	0.783 in
Series	Standard
Weight	2.723 lb
Seal Type	Molded Shroud
Base to Center Height H	42.86 mm
Total Length L	157.2 mm
Total Width A	1.563 in
Bolt Hole Spacing J	117.5 mm



BEARING INDIA PRIVATE LTD.

Bolt Hole Width N	14.3 mm
Bolt Hole Length N1	23.8 mm
Foot Height H1	16.7 mm
Total Height H2	83.3 mm
Dimension L1	52.4 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	8.7 mm
Dimension B1	1.406 in
Static Load Rating	2530 lbf
Dynamic Load Rating	4850 lbf